


NOTES:

- 1HP, 1PH/115VAC/, 50/60HZ, 3450RPM @ 60HZ, ODP
- 14.6 FL.AMP (60HZ), INSUL CLASS: B, TYPE KN, FRAME: H56 SPECIAL SHAFT, ENCL: TENNY, MOUNTING F1, RIGID BASE;
- SER. F. 1.00, FL EFF 70%, RATING 40C AMB-5 MIN;
- ROTATION: CLOCKWISE DRIVE END.
- MOMENTARY SWITCH;
- PRESS AND HOLD: MOTOR ON.



REV	DESCRIPTION	DATE	APPROVED
B	WAS 233/213 ADD SYMMETRY	1/26/05	GCS
A	ADD NAMEPLATE	7/2/03	GCS

UNLESS OTHERWISE SPECIFIED

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED

ASME Y14.5M - 1994

TOLERANCES: FRACTIONAL ± 1/32 ANGULAR ± 30'

DEQUALS ± 0.010 ± 0.005 ± 0.005 ± 0.005

BREAK ALL EDGES

ALL HOLES CHAMFERED 0.1x45°

SURFACE ROUGHNESS: 125µIN BEFORE PLATING

THIRD ANGLE PROJECTION

THIS DRAWING AND THE INFORMATION ON IT ARE THE PROPERTY OF HALLMARK INDUSTRIES, INC. AND IS NOT TO BE USED OR REPRODUCED WITHOUT PRIOR AUTHORIZATION

HALLMARK INDUSTRIES, INC.
733 BROADWAY ONE, SHANNON, I 60194 PHONE: (919)882-8821 FAX: (919)882-5669

TITLE: AC MOTOR, 56H, SLOTTED SHAFT
1HP, 115VAC/50/60HZ/1PH

DRAWN: GCS
DATE: 4/30/03
CHECKED: []
SCALE: 1:2
ALT. NO.:
SHEET: 1 OF 1