



SPECS:

1. 115VAC, 60HZ, 3.5" X 3.0" STUD MOUNTED
2. PRGY2 UL CONSTRUCTION/XEWR2 UL SPECIFIED THERMAL PROTECTOR
3. CLASS B INSULATION
4. 1/13HP, 1500RPM, 2.3A
5. CLOCKWISE ROTATION
6. 5/16" SHAFT DIAMETER - TAPERED END WITH BORE HOLE FOR 1/8" HEX SCREW
7. BALL BEARING
8. SINGLE SPEED

NOTES:

LEAD MATERIAL: 18 GA, 2/64 INS, 125°C
CROSS-LINKED POLYETHYLENE.
14.00/12.00 INCHES LONG WITH .58/.44 STRIP.

<p>UNLESS OTHERWISE SPECIFIED</p> <p>ALL DIMENSIONS ARE IN INCHES ANGLES UNLESS OTHERWISE SPECIFIED ASME Y14.5M - 1994</p> <p>DECIMALS: FRACTIONAL XX ± .010 ± 1/32 XXX ± .005 ANGULAR XXXX ± .0005 ± .30°</p> <p>TOLERANCES: FUNCTIONAL</p> <p>BREAK ALL EDGES ALL HOLES CHAMFERED .01" x 45° SURFACE ROUGHNESS: 125 µIN BEFORE PLATING THIRD ANGLE PROJECTION</p>		<p>THIS DRAWING AND THE INFORMATION ON IT ARE THE PROPERTY OF HALLMARK INDUSTRIES, INC. AND IS NOT TO BE USED OR REPRODUCED WITHOUT PRIOR AUTHORIZATION</p> <p>HALLMARK INDUSTRIES, INC. 733 BROADWAY ONE, SHANNON, I. 60194 PHONE: (616) 882-8821 FAX: (616) 882-5669</p>	
<p>TITLE AC MOTOR, SHADED POLE, 3.3" DIA 110V, 1/13HP, STUD MOUNTED</p>		<p>DRAWN T. ZHILIN</p>	
<p>SIZE DWG NO. B MA0207X</p>		<p>DRAWN DATE 5/20/04</p>	
<p>SCALE 1:1</p>		<p>CHECK DATE</p>	
<p>CUST. NO.</p>		<p>REV</p>	
<p>SHEET 1 OF 1</p>		<p>CHECK DATE</p>	